

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A pipe joint structure comprising:

a vessel provided at an outer circumference thereof with a first flat surface and at a circumferential wall thereof with a through-hole ~~whose~~ having one end is opened to the first flat surface and ~~whose another end is opened to an interior thereof of the vessel;~~

a joint fitting member ~~provided having in an interior thereof with an insertion hole whose inner diameter is larger than inner the diameter of the through-hole and a first screw thread at one of an inner circumferential wall of the insertion hole and or an outer circumferential wall thereof with a first screw thread, the joint fitting member being bonded to the vessel in such a manner so that the first flat surface is positioned radially inside the insertion hole and surrounds an entire outer periphery of the through-hole opened to the first flat surface;~~

a joint member provided with an insertion portion having (a) a second flat surface formed at an axial end thereof, ~~and with~~ (b) a pipe connection portion having a conical pressure receiving seat formed at another axial end thereof and (c) a pipe mounting screw thread at an outer circumference thereof, the insertion portion and the pipe connection portion being ~~provided through central parts thereof with a~~ connected by an internal fluid passage ~~whose with one end is opened to in the second flat surface and whose another end is opened to the conical pressure receiving seat;~~

a distribution pipe provided at an end thereof with a conical portion; and

a mounting nut fastened into the pipe mounting screw thread ~~in a state so that the conical portion is pressed against the conical pressure receiving seat,~~

wherein the joint member is further provided at ~~one of~~ a position inside the inner circumferential wall of the insertion hole ~~and or~~ a position outside the outer circumferential wall of the joint fitting member with a second screw thread screwed into the first screw thread so that the insertion portion is inserted into the insertion hole, ~~whereby~~ so that the second flat surface is pressed into against and in fluid tight contact directly or indirectly with the first flat surface ~~in a state that~~ while the fluid passage communicates with the through-hole.

2. (Currently Amended) ~~The~~ A pipe joint structure ~~according to~~ as in claim 1, wherein the first screw thread is a female thread formed on the inner circumferential wall of the insertion hole and the second screw thread is a male thread formed on an outer circumference of the insertion portion.

3. (Currently Amended) ~~The~~ A pipe joint structure ~~according to~~ as in claim 1, wherein the joint member is further provided outside the outer circumferential wall of the joint fitting member with a cylindrical portion~~pipe~~, and, further,

wherein the first screw thread is a male thread formed on the outer circumferential wall of the joint fitting member and the second screw thread is a female thread formed on an inner circumference of the cylindrical portion of the joint member~~pipe~~.

4. (Currently Amended) ~~The~~ A pipe joint structure ~~according to~~ as in claim 1, wherein the vessel is a common rail body for accumulating high pressure fuel in a common rail ~~type~~-fuel injection device.

5. (Currently Amended) ~~The A~~ pipe joint structure according to as in claim 4, wherein the fluid passage formed in the joint member has an orifice, which serves to reduce fluid flow pulsation generating in the distribution pipe.

6. (Currently Amended) ~~The A~~ pipe joint structure according to as in claim 1, further comprising:

a packing plate ~~having provided at a center thereof with a packing through-hole~~ constituting a part of the fluid passage, wherein the packing plate is disposed between the first and second flat surfaces so that the second flat surface is pressed against and in fluid tight contact with the packing plate which is in turn also pressed against and in fluid tight contact with the first flat surface via the packing plate.

7. (Currently Amended) ~~The A~~ pipe joint structure according to as in claim 1, wherein a part of the fluid passage positioned in the pipe connection portion immediately adjacent to the conical pressure receiving seat constitutes a hexagonal hole.

8. (Currently Amended) ~~The A~~ pipe joint structure according to as in claim 1, wherein the outer circumference of the pipe connection portion is provided with a plurality of grooves spaced circumferentially at given intervals and extending axially so as to cross the pipe mounting screw thread.

9. (Currently Amended) A method of assembling the joint member to the joint fitting member in the pipe joint structure according to claim 1, said method comprising steps of:

holding an end of the pipe connection portion and a part of ~~its~~ the outer circumference thereof on which the pipe mounting screw thread is provided; and

rotating the joint member relative to the joint fitting member so as to screw the second screw thread into the first screw thread so that the insertion portion is inserted ~~deep~~ into the insertion hole until the second flat surface is pressed against and in fluid tight contact with the first flat surface.

10. (Currently Amended) ~~The~~ A method of assembling the joint member to the joint fitting member in the pipe joint structure according to claim 9 ~~in use of~~ using a stad bolt fastening wrench having a box and a tool for rotatably driving the box, wherein an inner surface of the box is a screw fastened to the pipe mounting screw thread until an inner bottom of the box comes in contact with the end of the pipe connection portion so that the end of the pipe connection portion and the outer circumference thereof on a side of the conical pressure receiving seat is held by the box and, further, wherein the box is turned by the tool so as to apply a rotating moment to the pipe connection portion so that the joint member is rotated relative to the joint fitting member so as to screw the second screw thread into the first screw thread.

11. (Currently Amended) A method of assembling the joint member to the joint fitting member in the pipe joint structure according to claim 7 ~~in use of~~ using a wrench, said method comprising steps of:

inserting the wrench into the hexagonal hole; and

rotating the wrench so that rotational moment is applied to the pipe connection portion.

12. (Currently Amended) A method of assembling the joint member to the joint fitting member in the pipe joint structure according to claim 8 ~~in use of~~ using a wrench having a plurality of projections, comprising steps of:

inserting the projections of the wrench into the plurality of grooves; and

rotating the wrench so that rotational moment is applied to the pipe connection portion.